

# E1H0XXXN1043MR-CC

Jumper cable assemblies 5 meters or less manufactured with EC1-50-HF (1/4" HIFLEX) cable and soldered NEX10 male connector to right angle 4.3-10 male connector, with optional weatherproofing boots



## FEATURES

- **Superflexible jumper cable with soldered connectors**
- **Excellent return loss (VSWR) values**
- **Very low 3<sup>rd</sup> order intermodulation**

## Technical Features

### Electrical

Nominal impedance ( $\Omega$ )	50 $\pm$ 1
Frequency range (MHz)	10 – 6000
PIM ratio (2 x 20 W carrier 3 <sup>rd</sup> order) (dBc)	$\leq$ -153
Attenuation (dB/ft) at 20° C – without connectors*	
• 960 MHz	0.055
• 1880 MHz	0.079
• 2200 MHz	0.086
• 2700 MHz	0.096
• 3500 MHz	0.111
• 5800 MHz	0.148
Relative propagation velocity (%)	82
Maximum power rating (W)	100 W @ 2 GHz @ 85° C

### Mechanical

Minimum bending radius (in)	
• Single bend	1.0
• 15 repeated bends	1.0

**CONTACT US  
DIRECTLY FOR  
ORDERING &  
SUPPORT**

**EMAIL**  
CUSTOMERSERVICE@EUPEN.US

**WEB**  
EUPEN.US  
Radiating-cables.com

**CONTACT**  
PHONE 800.419.5100  
FAX 727.528.0751

**ADDRESS**  
5181 110<sup>TH</sup> Ave N, Unit D  
Clearwater, FL 33760



## Environmental

Temperature range (°C)	
• Installation	- 40 to + 60
• Operation	- 55 to + 85
Protection against water ingress	IP 68
General environmental	Corrosion and UV resistant
RoHS compliance	Yes

## Torque Specification (ft-lb)

4.3-10 male connector	6
NEX10 male connector	6

## Return Loss (dB)

Jumper length less than or equal to 5 meters	
0.0 – 3.0 GHz	≤ 24
3.1 – 6.0 GHz	≤ 20

## Optional Weatherproofing boot



### FEATURES

- **Additional IP68 protection**
- **Very quick and easy to install**
- **Repeated use**

## Product Reference

E1H0061N1043MR-CC

E1H	EC1-50-HF (1/4" HIFLEX)
0XXX	Length in centimeters (500 centimeters and below)
N10	NEX10 male connector ("B" in front of connector type includes factory installed weather boot)
43MR	4.3-10 male right angle connector ("B" in front of connector type includes factory installed weather boot)

\* Typical values without connectors, the typical connector attenuation (2 connectors) is less than 0.02 dB

**DIRECTLY FOR ORDERING & SUPPORT**

**EMAIL**  
CUSTOMERSERVICE@EUPEN.US

**WEB**  
EUPEN.US  
Radiating-cables.com

**CONTACT**  
PHONE 800.419.5100  
FAX 727.528.0751

**ADDRESS**  
5181 110<sup>TH</sup> Ave N, Unit D  
Clearwater, FL 33760