


EUCAHYBRID 100-4AWG4-2x24MM5

EUCAHYBRID 100-4AWG4-2x24SM

PRODUCT DESCRIPTION



1" hybrid fiber optic cable with 48V energy feeder in a corrugated aluminum shielding with UV resistant PE jacket. Multi mode and single mode fiber available.

TECHNICAL FEATURES

CONSTRUCTION	MM5	SM
Copper feed lines		
• Quantity	4	
• Conductor material	electrolytic copper	
• Section	21,3 mm ²	
Fiber Optic cable element		
• Quantity	2	
• Fibers quantity per element	24	
• Fiber type	Multi Mode	Single Mode
• Fiber size	50/125/900 µm	9/125/900 µm
• Reinforcement	Aramide fiber	
Outer shield		
• Material	Corrugated aluminum tube	
• Diameter	29,6 mm	
Jacket		
• Material	Black Polyethylene	
• Thickness	1,5 mm	
• Diameter	32,6 mm	



TECHNICAL DATA SHEET

Hybrid Cables for RRH applications

Kabelwerk | **EUPEN** AG

Rev.: 01/2020-05-25

cable

2/2

EUCAHYBRID 100-4AWG4-2x24MM5

EUCAHYBRID 100-4AWG4-2x24SM

MECHANICAL

• Minimum bending radius	326 mm
• Maximum pulling strength	150 daN
• Recommended temperature range	
Storage	-30 °C - +70 °C
Installation	-20 °C - +60 °C
Operation	-30 °C - +70 °C
• Maximum Hanger spacing	1,0 m
• Approx. weight	1460 kg/km (0,84 lb/ft)

ELECTRICAL

• Main conductors	
Resistance	0,86 Ohm/km at 20 °C
Operating DC voltage	48 V
Rated DC voltage	60 V

OPTICAL

MM5

SM

• Fiber type	OM3	G657A1
• Fiber wave length	850 & 1300 nm	1310 & 1550 nm
• Max attenuation		
	850 nm: ≤3,0 dB/km	1310 nm: ≤0,40 dB/km
	1300 nm: ≤1,0 dB/km	1550 nm: ≤0,25 dB/km
• Core diameter	50 µm	9 µm
• Cladding diameter	125 µm	125 µm
• Coating diameter	250 µm	250 µm
• Tight buffer fiber diameter	900 µm	900 µm